




ECOPIC® EV12

D A T A S H E E T

T H E D I S S U A S I V E P R O C E S S F O R B I R D S R E M O V A L



ECOPIC® EV12 is adapted to shutters having a maximum thickness of 3 cm, suitable for :


- Wood shutters
- Aluminium shutters

WARNING :

ECOPIC® EV12 must be installed on the outside face of the shutters.


The plastic base (polycarbonate) must be fixed at the edge of the shutters.

The spikes must exceed the maximum above the shutters for perfect efficiency.




MAIN FEATURES :

- Economical
- Ready to use
- Stainless steel spikes, quality spring 1 800 N/mm²
- Polycarbonate support, mass UV-stabilised and 100% virgin polycarbonate base
- Anti-UV treated and anti-fungal silicone SELFIXING® 280 ml



TECHNICAL DATAS : ECOPIC® EV12 :

- 3 units for 1 linear meter
- Size of unit : length. 36 x width 1 x height 11cm.
- Mass UV-stabilised and 100% virgin polycarbonate base (thermal résistance -100°C to +120°C)
- 12 spikes of 11cm
- 302 Stainless-steel wire / Steelinox®+ wire Ø 1,2 mm spikes.
- Holes on the strips : for screwing or nailing
- Width protected : up to 3cm.
- Protection : pigeons, sparrows and starlings.




PACKAGING :

- 20 linear meter, so 55 units.
- Packaging dimensions : 40 x 20 x 11cm box for 1,91 kg.

ECOPIC® RECOMMENDATIONS :

- Do not use this product on greasy or wet surfaces, or where the ambient temperature is under 5°C.
- Do not apply when surfaces have been (or will be) treated with water repellent. In general, check the compatibility with our products.




Adhesive : We recommend our SELFIXING® silicone adhesive, which is specially suited to use with ECOPIC® EV12.

Cleaning : To optimise the preparation of surfaces and to obtain a better guaranty, cleaning with our professional cleaner SELCLEANING®.

Guarantee : Refer to our website.

APPLICATION :

- ECOPIC® EV12 can be applied to any shutters (wood, aluminium, and more) with silicone, screws or nail.
- Before application the surface must be clean, dry, safe and solid.



INSTRUCTIONS FOR USE :

- See the installation sheet

ECOPIC

ZAC DU MOULIN
12 RUE DU MEUNIER
95700 ROISSY EN FRANCE

PHONE : +33.1.73.27.20.40
FAX : +33.1.30.11.24.55

EMAIL : ECOPIC@ECOPIC.COM

WWW.ECOPIC.COM

SAS AU CAPITAL DE 140 000€
401 788 120 RCS PONTOISE
SIRET 401 788 120 00046
APE 4690 Z
TVA FR 80 401 788 120